

# DHI-ARD812

## Panic Button



- Surface mount with screws.
- Works in a wide range of environments with a voltage that is no more than 250 VDC and a current that is no more than 300 mA.
- Works without a power supply.
- A reset key is included to quickly reset the device if necessary.

### System Overview

The device triggers alarms with the press of a button.

### Scene

Ideal for locations where alarms need to be manually triggered in emergencies, such as bank counters, accessible toilets and rooms for the elderly.

### Technical Specification

#### Port

Alarm Output 1, NC/NO, 250 VDC, Max. 300 mA

#### General

Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	≤95% (RH)
Product Dimensions	49.5 mm × 32.5 mm × 53.5 mm (1.95" × 1.28" × 2.11") (L × W × H)
Net Weight	34 g (0.07 lb)
Gross Weight	41.5 g (0.09 lb)
Installation	Surface mount
Casing Material	ABS
Appearance Color	Cineros
Certifications	CE
Anti-corrosion Level	Basic Protection
Storage Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Storage Humidity	≤95% (RH)
Packaging Dimensions	56.0 mm × 35.0 mm × 56.0 mm (2.20" × 1.38" × 2.20") (L × W × H)

### Ordering Information

Type	Model	Description
Panic Button	DHI-ARD812	Panic Button

### Dimensions (mm[inch])

