

Technical specifications

Compliance with standards	EN 50131 (Grade 2) PD 6662:2017	Connection to CMS	SurGard (Contact ID) SIA (DC-09) ADEMCO 685 Other proprietary protocols
Connected devices	up to 100 wireless devices Including up to 5 range extenders and up to 10 sirens.	Features	50 users 25 cameras or DVRs 32 automation scenarios 9 security groups photo verification support

Communication channels with Ajax devices	 Jeweller communication technology Frequency bands 866.0-866.5 MHz 868.0-868.6 MHz 868.7-869.2 MHz 905.0-926.5 MHz 915.85-926.5 MHz 921.0-922.0 MHz Depends on the sales region. Maximum effective radiated power (ERP) :::25 mW Communication range up to 2,000 m in an open space.	External communication channels	Ethernet 8P8C slot Up to 100 Mb/s. Cellular network 1 slot for micro-SIM 2G (GSM900/DCS1800 (83/88))
Power supply	Main power supply 100-240 V_r.J, 50/60 Hz Backup power supply Li-Ion battery with 2 A·h capacity Up to 16 hours of autonomous operation.	Installation	Operating temperature range from -10°C to +40°C Operating humidity up to 75% Protection class IP20
Enclosure	Colour white black Dimensions 163 x 163 x 36 mm Weight 362 g Tampering alarm	Complete set	Hub 2 (2G) Jeweller Power cable Ethernet cable SIM card Depends on the region of sale. Installation kit Quick Start Guide