

	Model	CP10000 / DLXCP10000
Input	Voltage Range	100 ~ 240 VAC
	Frequency Range	50 ~ 60 Hz
	Efficiency	≥88.0%@Rated voltage
	AC Current	2.0Amp
Output	Rated Voltage	DC 12V
	Rated Current	10A
	Current Range	0 ~ 10A
	Rated Power	120W
	Ripple & Noise	≤200mVpk
	Voltage Tolerance	±5%
	Line Regulation	≤0.1%
	Load Regulation	≤3%
Setup,Rise,Hold Up Time	230Vac Full load: ≤3S,≤100mS,≥5mS	
	Over Voltage	Power supply in the case of overvoltage can be automatically protected
	Over Current	110% ~ 200%@Rated current. Hiccup mode, recovers automatically after fault condition is removed.
	Short Circuit	No damage,Hiccup mode, recovers automatically after fault condition is removed.
Environment	Working Temp.,Humidity	Temp.: -10℃ ~ +40℃ ; Humidity: 10% ~ 95% RH, Non-condensing
	Storage Temp.,Humidity	Temp.: -20℃ ~ +85℃ ; Humidity: 10% ~ 95% RH, Non-condensing
Safety & EMC	Safety Standards	GB4943/EN62368/ETL62368/J62368
	Withstand Voltage	IP~OP: ≥1.5KVac
	Isolation Resistance	IP~OP: ≥100MΩ@500Vdc,25℃,70% RH
	EMC	GB/T9254/GB17625.1/EN55032/EN55035/J55032,IEC61000-4-2,IEC61000-4-4,IEC61000-4-5
Others	DC Plug	5.5*2.1*10mm
	DC Cable Length	1.5M
	Product Size	153.5*66.2*32.35mm
	Packing	40pcs/carton, 40.5*35*30CM
Certificate	ETL,CE,PSE,GS,UKCA,CCC	

