

	Model	CP2000-D-VI / DLXCP2000C
Input	Voltage Range	100 ~ 240 VAC
	Frequency Range	50 ~ 60 Hz
	Efficiency	≥86.2%@Rated voltage
	AC Current	0.8Amp
Output	Rated Voltage	DC 12V
	Rated Current	2A
	Current Range	0 ~ 2A
	Rated Power	24W
	Ripple & Noise	≤100mVpk
	Voltage Tolerance	±3%
	Line Regulation	≤0.1%
	Load Regulation	≤1%
Setup,Rise,Hold Up Time	230Vac Full load: ≤1S,≤1S,≥50mS	
	Over Voltage	120% ~ 130%@Rated voltage. Hiccup mode, recovers automatically after fault condition is removed.
	Over Current	120% ~ 150%@Rated current. Hiccup mode, recovers automatically after fault condition is removed.
	Short Circuit	No damage,Hiccup mode, recovers automatically after fault condition is removed.
Environment	Working Temp.,Humidity	Temp.: -10℃ ~ +40℃ ; Humidity: 10% ~ 95% RH, Non-condensing
	Storage Temp.,Humidity	Temp.: -20℃ ~ +85℃ ; Humidity: 10% ~ 95% RH, Non-condensing
Safety & EMC	Safety Standards	UL/CB/CE: EN/IEC 62368-1; EN/IEC 60950-1
	Withstand Voltage	IP~OP: ≥3KVac
	Isolation Resistance	IP~OP: ≥100MΩ@500Vdc,25℃,70% RH
	EMC	FCC/Part 15 ;EN55032、 EN55035; EN/IEC61000
Others	DC Plug	5.5*2.1*10mm
	DC Cable Length	1.2M
	Product Size	98.5*46.8*32mm
	Packing	100pcs/carton, 56*33*33CM
Certificate	UL,CE,FCC,RoHs,CEC,ERP	

