

DHI-LM32-F200

32" FHD Monitor



Features :

- Light and cost-effective plastic housing
- suitable for continuous 24/7 operation
- 178°H/178°V extra-wide viewing angle for overall viewing performance
- High fidelity digital processing for a brilliant and vivid video
- 8ms fast response time with no image blurring or ghosting
- Support multiple signal inputs such as HDMI, VGA and USB
- Built-in speakers
- Physical button and infrared remote dual control mode



Technical Specification

Model

Model	DHI-LM32-F200
-------	---------------

Display

Screen Size	31.55"
Aspect Ratio	16:9
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance	200 cd/㎡
Contrast	1400:1
Display Color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	8ms
Refresh Rate	60Hz

Signals

Input	VGA(D-Sub)×1, HDMI×1, USB×1	
Output	Speaker	8W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	55W	
Consumption (Standby)	≤0.5W	
Net Weight	3.9kg (8.6lb)	
Gross Weight	5.1kg (11.2lb)	
Bezel Width	13.9mm (U/R/L), 20.5mm (B)	
Wall Mount	75×75mm (3.0"×3.0")	
Dimension without standard (W×H×D)	731.4×432.6×67.5mm (28.8"×17"×2.7")	
Package(W×H×D)	797×483×108mm (31.4"×19.0"×4.3")	
Work Environment	Temperature	0℃~40℃ (32°F~104°F)
	Humidity	10%~85%

Accessory

Standard	HDMI cable, power cable, remote control, pedestal
Optional	Hanging bracket

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

