

DH-PFM976-531-PT

UTP CAT5E 15U" Pass Through RJ45 Connector



- Unshielded CAT5E RJ-45 connector.
- Designed with a through hole for cables to be fed through.
- Built with trident brass sheet and 15U" gold plating.
- Lifespan of 750 cycles.

Technical Specification

Material

Material	PC + brass
Gold Plating Thickness	15U"
Flammability Rating	UL94V-2

Electrical

Operating Voltage	150 VAC RMS
Operating Current	1.5 AMP
Contact Resistance	≤ 20 mΩ
Insulation Resistance	≥1000 MΩ@500 VDC
Withstands Voltage between Terminals	1000 VDC/VAC PEAK @0.5 mA 50 Hz or 60 Hz 1 Minute

Mechanical

Retention Strength	50 N for 60 s ± 5 s
Lifespan	750 times
Insertion Force	≤ 30 N

Environmental

Operating Temperature	-25 °C to +55 °C (-13 °F to +131 °F)
Storage Temperature	-10 °C to +40 °C (+14 °F to +104 °F)
Storage Humidity	≤ 80%
Storage Time	12 months

Structural

Single Strand Cable Diameter	23 AWG–24 AWG
Single Strand Insulated Cable Diameter	0.89 mm–1.00 mm (0.035"–0.039")

Outer Sheath Diameter	≤ 5.4 mm (0.21")
Packaging Dimensions	120 mm × 65 mm × 90 mm (4.72" × 2.55" × 3.54")
Transport Package Dimensions	500 mm × 350 mm × 270 mm (19.69" × 13.78" × 10.63")
Packaging Method	100 pcs in 1 carton, and 50 cartons in 1 package
Net Weight	0.17 kg (0.37 lb)
Gross Weight	0.21 kg (0.46 lb)

Ordering Information

Type	Model	Description
Cabling Accessory Series	DH-PFM976-531-PT	UTP CAT5E 15U" Pass Through RJ45 Connector

Dimensions (mm [inch])

