

# DHI-DAE-HC5711GW-T5

## Dash Camera



### System Overview

The Dahua DHI-DAE-HC5711GW-T5 Dash Camera is a high resolution automotive dash camera that features easy installation and operation. The device can be communicated with its DH Dashcam app through built-in Wi-Fi.

The built-in G-Sensor can automatically lock the currently recording video when it senses a crash or strong vibration to prevent the video from being overwritten. MicroSD cards up to 128 GB are supported. The built-in mic and speaker can be used to record, play back and voice control.

### Highlights

- 3840×2160P ultra high resolution image
- F1.5 iris offers crisp night imaging
- Built-in Wi-Fi AP module
- G-Sensor module supports collision detection and video lock
- Supports MicroSD card up to 128 GB
- Compatible with mobile client for setup, live view, recording search and backup
- Voice control
- Front-rear record

### Scene

Suitable for consumer driving records.

### Technical Specification

#### Camera

|               |                                                             |
|---------------|-------------------------------------------------------------|
| Image Sensor  | 1/2.8" CMOS                                                 |
| Resolution    | Front: 3840×2160P@25FPS<br>Rear: 1920×1080P@25FPS           |
| Field of View | Front: D=123°, H=105°, V=56°<br>Rear: D=136°, H=111°, V=58° |

|                      |                           |
|----------------------|---------------------------|
| Iris                 | Front: F1.5<br>Rear: F1.8 |
| Video Compression    | H.265                     |
| OSD                  | Display time, date, etc.  |
| Image format         | JPEG                      |
| Storage              | 1 TF card (up to 128GB)   |
| Communication Module | WiFi AP                   |
| G-sensor             | G-Sensor                  |
| Screen               | 9.66"(1920×480dpi)        |

#### Interface

|              |                     |
|--------------|---------------------|
| Power Supply | Type C              |
| Audio Input  | Build-in microphone |
| Audio Output | Build-in speaker    |

#### General

|                       |                                     |
|-----------------------|-------------------------------------|
| Operating Temperature | -20°C to 70°C (-4°F to 158°F)       |
| Operating Humidity    | <95%(No condensation)               |
| Power Supply          | 5V DC/3A                            |
| Power Consumption     | ≤15W                                |
| Dimensions            | 256mm×73mm×40mm(10.07"×2.87"×1.57") |
| Weight                | Approx. 338.4 g (0.75 lb.)          |

#### Dimension (mm[inch])

